

Setup Linux ssh for key based login

We need to create a private/public key set to allow passwordless login via ssh. To do this run the ssh-keygen command:

```
$ ssh-keygen -t ecdsa
Generating public/private ecdsa key pair.
Enter file in which to save the key (/home/testuser1/.ssh/id_ecdsa):
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/testuser1/.ssh/id_ecdsa
Your public key has been saved in /home/testuser1/.ssh/id_ecdsa.pub
The key fingerprint is:
SHA256:xb4Rs37UbXt3Wn5cHkdKWY2ZDBbor9F83IYNLhjsfIU
testuser1@bree.strw.leidenuniv.nl
The key's randomart image is:
+---[ECDSA 256]---+
|           ...      |
|          .. o      |
|         o=. + o.   |
|        o++E.O.+   |
|       So+*.=. @o   |
|      .+=* BoB     |
|      o+.o =0      |
|       ..  +B      |
|       . o         |
+-----[SHA256]-----+
```

For both question about passphrase, just hit enter (we will not be using passphrases). This will also have generated two files in your personal .ssh directory:

```
$ ls -ltr id_ecdsa*
-rw----- 1 testuser1 users 537 Mar 22 12:13 id_ecdsa
-rw-r--r-- 1 testuser1 users 195 Mar 22 12:13 id_ecdsa.pub
```

The file id_ecdsa.pub must be transferred to the remote host. For this we can use ssh-copy-id:

```
$ ssh-copy-id -i ~/.ssh/id_ecdsa.pub username@remote-host
```

This may produce the following message:

```
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed:
"/home/username/.ssh/id_ecdsa.pub"
The authenticity of host 'remote-host (123.123.123.123)' can't be
established.
ECDSA key fingerprint is SHA256:tygMarTe3S0jTcY9HzldKThxQzsTeiYHg5JmjB2bxeg.
Are you sure you want to continue connecting (yes/no)? yes
```

Having confirmed the access key to remote-host, the copy operation will commence:

```
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to
filter out any that are already installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are
prompted now it is to install the new keys
username@remote-host's password:
```

Type your password to actually start the file copy.

```
Number of key(s) added: 1
```

```
Now try logging into the machine, with:  "ssh 'username@remote-host'"
and check to make sure that only the key(s) you wanted were added.
```

The passwordless ssh login is now in place.

Alternative public key copy

It may be that ssh-copy-id is not available with your version of OpenSSH. In that case you need to copy the information yourself. This can be done following the below procedure.

It is possible to copy the public key directly to the remote host. The command below pipes the content of the public key through the ssh login to the remote host. On the remote host we first create the .ssh directory (if not there) and then append the public key content to the authorized_keys file, all in one command:

```
cat ~/.ssh/id_ecdsa.pub | ssh username@remote-host "mkdir -p ~/.ssh && chmod
700 ~/.ssh && cat >> ~/.ssh/authorized_keys"
```

where username@remote-host can also be replaced by the logical name you have defined while configuring the ssh.

After successful execution of above command you can login to remote-host without specifying a password.

From:
<https://helpdesk.lorentz.leidenuniv.nl/wiki/> - **Computer Documentation Wiki**

Permanent link:
<https://helpdesk.lorentz.leidenuniv.nl/wiki/doku.php?id=services:2fa:ssh:linux&rev=1616419914>

Last update: **2021/03/22 13:31**

